(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 21 October 2004 (21.10.2004)

PCT

(10) International Publication Number WO 2004/089741 A1

(51) International Patent Classification7: F15D 1/02, 1/12

B64C 1/38,

(21) International Application Number:

PCT/FI2004/000211

7 April 2004 (07.04.2004) (22) International Filing Date:

(25) Filing Language:

Finnish

(26) Publication Language:

English

(30) Priority Data: 20030538

10 April 2003 (10.04.2003)

(71) Applicant and

(72) Inventor: PULKKA, Esko [FI/FI]; Pahasaarentie 156 G, FI-45910 Voikkaa (FI).

(74) Agent: HEINÄNEN OY; Annankatu 31-33 C, FI-00100 Helsinki (FI).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:


of inventorship (Rule 4.17(iv)) for US only

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD FOR REDUCING KINETIC FRICTION



(57) Abstract: This specification describes a method for reducing kinetic friction by means of profiled surface patterns when devices and appliances of different materials, sizes and shapes are in contact with air, gas and liquid masses. The method can be used above all to achieve savings in energy consumption in means of transport by providing their surfaces with profiled surface patterns. The method is also suited for use in numerous other applications where kinetic friction between the aforesaid masses and devices and appliances is to be reduced for a specific reason, but those are not covered by the scope of this application.

